

PVC
FRPVC (red stripe)
LHPVC (red stripe)

F4CC...
...001
...002

Primary group code
Finish code

Copper 37 Core
600/1000V
SANS 1507

Size code	...naaa...	D910	D915	D925
Conductor size	mm ² nom	1.0	1.5	2.5
Conductor diameter	mm app.	1.3	1.6	2.1
Insulation diameter	mm app.	2.9	3.2	3.7
Cable diameter	mm app.	24.5	26.5	29.5
Cable mass	kg/m app.	0.65	1.90	1.20
Gross mass (500 m)	kg app.	485	640	845
Bending radius	mm min.	196	212	236
Resistance				
dc @ 20°C	Ω/km max	18.10	12.10	7.41
ac @ 70°C	Ω/km max	21.66	14.48	8.87
Reactance	Ω/km	0.116	0.110	0.103
Capacitance	μF/km	0.275	0.315	0.375
Impedance	Ω/km	21.657	14.478	8.867
(Single Phase) Volt Drop	mV/A/m	43.31	28.96	17.73

Last updated May 2006

When ordering please quote: primary + size + finish code
e.g. F4CC D925 001



POWER BY INNOVATION... INNOVATION THROUGH PARTNERSHIPS

A member of the REUNERT Group

CBi Electric African Cables
PO Box 172, Vereeniging 1930 • Tel: +27 16 430 6000 • Fax: +27 16 423 6103
www.cbi-electric.com • afcab@cbi-electric.com

