

PVC
FRPVC (red stripe)
LHPVC (blue stripe)

F4CC...
...001
...002

Primary group code
Finish code

Copper 7 Core
600/1000 V
SANS 1507

Size code	...naaa...	7910	7915	7925	7004	7006	7010
Conductor size	mm ² nom	1	1.5	2.5	4	6	10
Conductor diameter	mm app.	1.3	1.7	2.2	2.5	3	4
Insulation diameter	mm app.	2.9	3.5	4	5	5.5	6
Cable diameter	mm app.	12	13	15	17	19	21.5
Cable mass	kg/m app.	0.2	0.25	0.35	0.5	0.65	1
Gross mass (500 m)	kg app.	130	155	215	305	385	560
Bending radius	mm min.	96	104	120	136	152	172
Resistance							
dc @ 20°C	Ω/km max	18.1	12.1	7.41	4.61	3.08	1.83
ac @ 70°C	Ω/km max	21.657	14.478	8.867	5.517	3.687	2.192
Reactance	Ω/km	0.116	0.11	0.103	0.103	0.097	0.091
Capacitance	μF/km	0.275	0.315	0.375	0.376	0.44	0.532
Impedance	Ω/km	21.657	14.478	8.867	5.517	3.687	2.192
(Single Phase) Volt Drop	mV/A/m	43.31	28.96	17.73	11.03	7.37	4.38

Last updated May 2006

When ordering please quote: primary + size + finish code
e.g. F4CC 7910 001



POWER BY INNOVATION... INNOVATION THROUGH PARTNERSHIPS

A member of the REUNERT Group

CBi Electric African Cables
PO Box 172, Vereeniging 1930 • Tel: +27 16 430 6000 • Fax: +27 16 423 6103
www.cbi-electric.com • afcab@cbi-electric.com

