

PILC/PILAC
FRPVC (red stripe)
LHPVC (blue stripe)

FIFC... Primary group code
...30 001 Table + Finish code
...30 002

Copper I Core
6350/11000V
Table 10
SANS 97

Size code	...naaa...	1150	1185	1240	1300	1400	1500	1630	1800	1999
Conductor size	mm ² nom	150	185	240	300	400	500	630	800	1000
Conductor diameter	mm app	14.7	16.5	18.8	21.2	23.9	27.4	30.3	34.2	38.9
Insulated diameter	mm app	22.7	24.5	26.8	29.2	31.9	35.4	38.3	42.2	47.0
Diameter over lead sheath	mm app	28.0	30.0	32.5	35.0	37.5	41.5	44.5	49.0	53.5
Overall diameter	mm app	31.0	33.0	35.5	38.0	41.0	45.0	48.5	53.0	58.0
Cable mass	kg/m app.	3.4	3.9	4.7	5.5	6.6	8.1	9.9	12.1	14.7
Gross mass (drum length)	kg app.	2200	2450	2850	3250	3800	4550	5450	6550	7850
Bending radius	mm min.	620	660	710	760	820	900	970	1060	1160
Current rating										
In ground	Amps	325	365	425	480	540	610	680	750	880
In ducts	Amps	295	335	385	435	490	550	615	670	790
In air	Amps	370	430	505	580	675	780	885	995	1210
Positive sequence										
Resistance dc @ 20°C	Ω/km max	0.1240	0.0991	0.0754	0.0601	0.0470	0.0366	0.0283	0.0221	0.0176
ac @ 70°C	Ω/km max	0.149	0.120	0.0918	0.0740	0.0590	0.0474	0.0386	0.0322	0.0228
Reactance	Ω/km	0.111	0.107	0.103	0.097	0.095	0.092	0.089	0.087	0.085
Impedance	Ω/km	0.186	0.160	0.138	0.122	0.112	0.103	0.097	0.093	0.088
Zero sequence										
Resistance	Ω/km	1.880	1.735	1.487	1.365	1.177	1.006	0.880	0.761	0.653
Reactance	Ω/km	0.057	0.054	0.051	0.045	0.043	0.040	0.038	0.036	0.034
Impedance	Ω/km	1.881	1.736	1.488	1.366	1.178	1.007	0.881	0.762	0.654
Short circuit ratings										
Symmetrical	kA (1sec)	21.5	26.9	35.3	44.3	56.7	72.8	94.1	121	151
Earth fault (Symmetrical limit)	kA (1sec)	3.6	3.9	4.5	4.9	5.6	6.5	7.4	8.6	9.9

Last updated May 2006

When ordering please quote: primary + size + table + finish code
e.g. FIFC 1500 30 001



POWER BY INNOVATION... INNOVATION THROUGH PARTNERSHIPS

A member of the REUNERT Group

CBI Electric African Cables
PO Box 172, Vereeniging 1930 • Tel: +27 16 430 6000 • Fax: +27 16 423 6103
www.cbi-electric.com • afcab@cbi-electric.com

