

Low Voltage PVC Control Cables

PVC
 FRPVC (red stripe)
 LHPVC (blue stripe)

F4CC...
 ...001
 ...002

Primary group code
 Finish code

Copper 12 Core
 600/1000 V
 SANS 1507

Size code	...naaa...	A910	A915	A925	A004
Conductor size	mm ² nom	1	1.5	2.5	4
Conductor diameter	mm app.	1.3	1.6	2	2.5
Insulation diameter	mm app.	2.9	3.2	3.7	4.5
Cable diameter	mm app.	16	17	18.5	22.5
Cable mass	kg/m app.	0.35	0.4	0.55	0.8
Gross mass (500 m)	kg app.	215	260	335	460
Bending radius	mm min.	156	164	188	224
Resistance					
dc @ 20°C	Ω/km max	18.1	12.1	7.41	4.61
ac @ 70°C	Ω/km max	21.66	14.48	8.87	5.52
Reactance	Ω/km	0.116	0.11	0.103	0.103
Capacitance	μF/km	0.275	0.315	0.375	0.376
Impedance	Ω/km	21.66	14.48	8.867	5.517
(Single Phase) Volt Drop	mV/A/m	43.31	28.96	17.73	11.03

Last updated May 2006

When ordering please quote: primary + size + finish code
 e.g. F4CC A910 001



POWER BY INNOVATION... INNOVATION THROUGH PARTNERSHIPS

CBi Electric African Cables
 PO Box 172, Vereeniging 1930 • Tel: +27 16 430 6000 • Fax: +27 16 423 6103
www.cbi-electric.com • afcab@cbi-electric.com

A member of the REUNERT Group

