

PILC  
FRPVC DTA FRPVC (red stripe)  
LHPVC DTA LHPVC (blue stripe)

FIJC... Primary group code  
...21191 Table + Finish code  
...21292

Copper 3 Core  
19000/33000V  
Table 21  
SANS 97

Size code	...naaa...	3095	3120	3150	3185	3240	3300
Conductor size	mm <sup>2</sup> nom	95	120	150	185	240	300
Conductor diameter	mm app.	11.8	13.2	14.7	16.5	18.8	21.2
Insulated diameter	mm app.	26.8	28.2	29.7	31.5	33.8	36.2
Diameter over lead sheath	mm app.	65.0	68.5	72.0	76.0	81.5	87.0
Bedding diameter	mm app.	69.0	72.0	76.0	80.0	85.5	91.5
Thickness of DSTA	mm	0.80	0.80	0.80	0.80	0.80	0.80
Overall diameter	mm app.	79.0	82.5	86.5	91.0	96.5	103.0
Normal drum length	m	300	300	300	300	300	300
Cable mass	kg/m app.	13.7	15.3	17.0	19.2	22.2	25.8
Gross mass (drum length)	kg app.	4610	5090	5600	6260	7160	8240
Bending radius	mm min.	1185	1238	1298	1365	1448	1545
<b>Current rating</b>							
In ground	Amps	230	260	295	330	380	420
In ducts	Amps	200	225	250	285	325	360
In air	Amps	255	290	330	375	435	495
<b>Positive sequence</b>							
Resistance dc @ 20°C	Ω/km max	0.193	0.153	0.124	0.0991	0.0754	0.0601
ac @ 70°C	Ω/km max	0.231	0.184	0.149	0.1198	0.0919	0.0741
Reactance	Ω/km	0.115	0.111	0.108	0.104	0.100	0.097
Impedance	Ω/km	0.258	0.215	0.184	0.158	0.136	0.121
<b>Zero sequence</b>							
Resistance	Ω/km	1.649	1.477	1.332	1.192	1.058	0.914
Reactance	Ω/km	0.118	0.115	0.111	0.108	0.104	0.101
Impedance	Ω/km	1.653	1.482	1.337	1.197	1.063	0.919
<b>Short circuit ratings</b>							
Symmetrical	kA (1sec)	13.8	17.4	21.5	26.9	35.3	44.3
Earth fault (Symmetrical limit)	kA (1sec)	12.3	13.4	14.7	16.2	18.0	20.7

Last updated May 2006

When ordering please quote: primary + size + table + finish code  
e.g. FIJC 3120 21 191



POWER BY INNOVATION... INNOVATION THROUGH PARTNERSHIPS

A member of the REUNERT Group

**CBI Electric African Cables**  
PO Box 172, Vereeniging 1930 • Tel: +27 16 430 6000 • Fax: +27 16 423 6103  
www.cbi-electric.com • afcab@cbi-electric.com

