

Aluminium 3 Core
6600/6600V
Table 24
SANS 97

PILC/PILAC
FRPVC DTA FRPVC (red stripe) ...24191
LHPVC DTA FRPVC (blue stripe) ...24292

FIEA... Primary group code
...24191 Table + Finish code
...24292

Size code	...naaa...	3016	3025	3035	3050	3070	3095	3120	3150	3185	3240	3300
Conductor size	mm ² nom	16*	25*	35*	50*	70	95	120	150	185	240	300
Conductor depth	mm app.	5.2	5.9	7.0	8.3	8.3	9.8	11.0	12.2	13.7	15.7	17.6
Insulated depth	mm app.	10.2	10.9	12.0	13.3	13.3	14.8	16.0	17.2	18.7	20.7	22.6
Diameter over lead sheath	mm app.	30.5	32.0	34.5	38.0	37.5	40.5	43.5	46.0	49.5	54.0	58.5
Bedding diameter	mm app.	33.0	35.0	37.5	41.0	40.5	44.0	47.0	49.5	53.0	58.0	62.5
Size of armour wires	mm	0.80	0.80	0.80	0.80	0.80	0.80	0.80	0.80	0.80	0.80	0.80
Overall diameter	mm app.	41.0	43.0	45.5	49.5	49.0	52.5	56.5	59.0	62.5	68.0	73.0
Normal drum length	m	500	500	500	300	300	300	300	300	300	300	300
Cable mass	kg/m app.	3.7	4.1	4.7	5.4	5.7	6.5	7.4	8.1	9.1	10.9	12.4
Gross mass (drum length)	kg app.	2210	2410	2710	1950	2040	2280	2550	2760	3080	3690	4250
Bending radius	mm min.	492	516	546	594	588	630	678	708	750	816	876
Current rating												
In ground	Amps	69	88	105	125	155	185	210	240	270	320	360
In ducts	Amps	59	75	90	110	130	160	180	205	230	270	305
In air	Amps	68	88	110	130	160	195	225	260	300	350	405
Positive sequence												
Resistance dc @ 20°C	Ω/km max	1.910	1.200	0.868	0.641	0.443	0.320	0.253	0.206	0.164	0.125	0.100
ac @ 80°C	Ω/km max	2.372	1.490	1.078	0.796	0.550	0.398	0.315	0.257	0.205	0.157	0.126
Reactance	Ω/km	0.109	0.105	0.100	0.095	0.077	0.073	0.071	0.069	0.067	0.065	0.063
Impedance	Ω/km	2.374	1.494	1.083	0.802	0.556	0.404	0.323	0.266	0.215	0.169	0.140
Zero sequence												
Resistance	Ω/km	7.826	6.269	5.208	4.341	3.945	3.340	2.922	2.710	2.372	1.956	1.715
Reactance	Ω/km	0.153	0.147	0.139	0.131	0.134	0.127	0.122	0.118	0.113	0.108	0.104
Impedance	Ω/km	7.828	6.271	5.210	4.343	3.947	3.342	2.924	2.712	2.375	1.959	1.718
Short circuit ratings												
Symmetrical	kA (1sec)	1.4	2.3	3.1	4.2	6.1	8.5	10.7	13.2	16.6	21.7	27.2
Earth fault (Symmetrical limit)	kA (1sec)	3.2	3.6	4.2	4.9	5.1	5.9	6.7	7.1	8.0	9.7	10.9

Last updated May 2006

* Circular Conductor

When ordering please quote: primary + size + table + finish code
e.g. FIEA 3120 24 191



POWER BY INNOVATION... INNOVATION THROUGH PARTNERSHIPS

A member of the REUNERT Group

Cbi Electric African Cables
PO Box 172, Vereeniging 1930 • Tel: +27 16 430 6000 • Fax: +27 16 423 6103
www.cbi-electric.com • afcab@cbi-electric.com

